



# 俊英科技（上海）有限公司

中国上海市宜山路900号科技大楼C区1001室 邮编:200233

电话: (021) 64958888

传真: (021) 54235889

## 低通滤波器

型号	截止频率 (MHz)	通带 (MHz)	插入损耗 (dB)	驻波比 (: 1)	抑制频带 (MHz)		尺寸 (mm <sup>3</sup> ) 长x宽x高
					衰减 > 20dB	衰减 > 30dB	
WGLL-00080	80	DC~80	≤1.2	≤1.5	200-4500	225-1550	3.2x1.6x1.0
WGLL-00180	180	DC~180	≤1.2	≤1.5	400-6000	460-2910	3.2x1.6x1.0
WGLL-00190	190	DC~190	≤1.2	≤1.5	410-3740	510-2910	3.2x1.6x1.0
WGLL-00225	225	DC~225	≤1.2	≤1.5	470-3900	600-2300	3.2x1.6x1.0
WGLL-00320	320	DC~320	≤1.2	≤1.5	560-5000	700-3700	3.2x1.6x1.0
WGLL-00400	400	DC~400	≤1.2	≤1.5	660-5500	680-3000	3.2x1.6x1.0
WGLL-00530	530	DC~530	≤1.2	≤1.5	820-5000	860-3000	3.2x1.6x1.0
WGLL-00575	575	DC~575	≤1.2	≤1.5	900-5500	1050-3200	3.2x1.6x1.0
WGLL-00630	630	DC~630	≤1.2	≤1.5	970-6000	1050-3500	3.2x1.6x1.0
WGLL-00800	800	DC~800	≤1.3	≤1.5	1400-5000	1500-4600	3.2x1.6x1.0
WGLL-00900	900	DC~900	≤1.3	≤1.5	1400-6500	1450-5400	3.2x1.6x1.0
WGLL-01000	1000	DC~1000	≤1.0	≤1.5	1500-6000	200-5500	3.2x1.6x1.0
WGLL-01200 Freq. Cut-off: 1580MHz	1200	DC~1200	≤1.2	≤1.5	1800-6500	2000-6000	3.2x1.6x1.0
WGLL-01200-A Freq. Cut-off: 1450MHz	1200	DC~1200	≤1.2	≤1.5	1800-6500	2000-6000	3.2x1.6x1.0
WGLL-01325-A	1325	DC~1325	≤1.0	≤1.5	2100-6000	2200-5500	3.2x1.6x1.0
WGLL-01400-A	1400	DC~1400	≤1.0	≤1.5	1975-6800	2500-5500	3.2x1.6x1.0
WGLL-01500	1500	DC~1500	≤1.3	≤2.0	1970-6800	2000-6600	3.2x1.6x1.0
WGLL-01700-A	1700	DC~1700	≤1.0	≤1.5	2500-7000	3000-6500	3.2x1.6x1.0
WGLL-01800	1800	DC~1800	≤1.3	≤2.0	2350-7500	2500-7200	3.2x1.6x1.0
WGLL-02250	2250	DC~2250	≤1.3	≤1.5	2850-7200	3000-6000	3.2x1.6x1.0
WGLL-02400	2400	DC~2400	≤1.5	≤1.5	3600-5000	3700-4000	3.2x1.6x1.0
WGLL-02500	2500	DC~2500	≤1.3	≤1.5	3675-8000	3800-6100	3.2x1.6x1.0
WGLL-02600	2600	DC~2600	≤1.3	≤1.5	3560-8400	3900-8000	3.2x1.6x1.0
WGLL-03000	3000	DC~3000	≤0.9	≤1.5	4200-6000 & 8000	> 25dB @4200-6000	3.2x1.6x1.0
WGLL-03400	3400	DC~3400	≤1.2	≤1.5	4550-8000	4790-6000	3.2x1.6x1.0
WGLL-03500	3500	DC~3500	≤1.2	≤1.5	4550-8000	4790-6000	3.2x1.6x1.0
WGLL-03600	3600	DC~3600	≤1.2	≤1.5	4550-8000	4790-6000	3.2x1.6x1.0
WGLL-03700	3700	DC~3700	≤1.2	≤1.5	4550-8000	4790-6000	3.2x1.6x1.0
WGLL-03900	3900	DC~3900	≤1.5	≤1.5	6000-13000	6250-8300	3.2x1.6x1.0

Ver.20190816