



# 俊英科技（上海）有限公司

中国上海市宜山路900号科技大楼B区904室 邮编:200233  
电话: (021) 64958888 传真: (021) 54235889

## 低通滤波器

型号	截止频率 (MHz)	通带 (MHz)	插入损耗 (dB)	驻波比 (: 1)	抑制频带 (MHz)		尺寸 (mm <sup>3</sup> ) 长x宽x高
					衰减 > 20dB	衰减 > 30dB	
WGLL-00080	80	DC~80	≤1.2	≤1.5	200-4500	225-1550	3.2x1.6x1.0
WGLL-00095-A	95	DC~95	≤1.2	≤1.5	240-4500	255-1600	3.2x1.6x1.0
WGLL-00105-A	105	DC~105	≤1.2	≤1.5	250-4750	265-1650	3.2x1.6x1.0
WGLL-00120-A	120	DC~120	≤1.2	≤1.5	280-4750	300-1850	3.2x1.6x1.0
WGLL-00160-A	160	DC~160	≤1.2	≤1.5	330-6100	480-2700	3.2x1.6x1.0
WGLL-00180-A	180	DC~180	≤1.2	≤1.5	370-6400	525-2350	3.2x1.6x1.0
WGLL-00190-A	190	DC~190	≤1.2	≤1.5	400-6550	510-2850	3.2x1.6x1.0
WGLL-00225-A	225	DC~225	≤1.5	≤1.5	460-5500	510-2500	3.2x1.6x1.0
WGLL-00320-A	320	DC~320	≤1.2	≤1.5	560-5300	640-2500	3.2x1.6x1.0
WGLL-00400	400	DC~400	≤1.2	≤1.5	660-5500	680-3000	3.2x1.6x1.0
WGLL-00490-A	490	DC~490	≤1.5	≤1.5	800-6000	880-2500	3.2x1.6x1.0
WGLL-00530-A	530	DC~530	≤1.5	≤1.5	820-6000	940-3000	3.2x1.6x1.0
WGLL-00575-A	575	DC~575	≤1.5	≤1.5	900-5500	1050-3200	3.2x1.6x1.0
WGLL-00630-A	630	DC~630	≤1.5	≤1.5	1000-6000	1050-3500	3.2x1.6x1.0
WGLL-00800-A	800	DC~800	≤1.3	≤1.5	1400-5000	1500-4600	3.2x1.6x1.0
WGLL-00900	900	DC~900	≤1.3	≤1.5	1400-6500	1450-5400	3.2x1.6x1.0
WGLL-01000-A	1000	DC~1000	≤1.0	≤1.5	1500-6000	200-5500	3.2x1.6x1.0
WGLL-01200	1200	DC~1200	≤1.2	≤1.5	1800-6500	2000-6000	3.2x1.6x1.0
WGLL-01325-A	1325	DC~1325	≤1.0	≤1.5	2100-6000	2200-5500	3.2x1.6x1.0
WGLL-01400-A	1400	DC~1400	≤1.0	≤1.5	1975-6800	2500-5500	3.2x1.6x1.0
WGLL-01500	1500	DC~1500	≤1.3	≤2.0	1970-6800	2000-6600	3.2x1.6x1.0
WGLL-01575-A	1575	DC~1575	≤1.3	≤1.5	2175-7100	2225-6800	3.2x1.6x1.0
WGLL-01700-A	1700	DC~1700	≤1.0	≤1.5	2500-7000	3000-6500	3.2x1.6x1.0
WGLL-01800	1800	DC~1800	≤1.3	≤2.0	2350-7500	2500-7200	3.2x1.6x1.0
WGLL-02250	2250	DC~2250	≤1.3	≤1.5	2850-7200	3000-6000	3.2x1.6x1.0
WGLL-02400	2400	DC~2400	≤1.5	≤1.5	3600-5000	3700-4000	3.2x1.6x1.0
WGLL-02500	2500	DC~2500	≤1.3	≤1.5	3675-8000	3800-6100	3.2x1.6x1.0
WGLL-02600	2600	DC~2600	≤1.3	≤1.5	3560-8400	3900-8000	3.2x1.6x1.0
WGLL-03000-B	3000	DC~3000	≤1.3	≤1.5	3450-9250	3740-3940 & 4900-9100	3.2x1.6x1.0
WGLL-03600-A	3600	DC~3600	≤0.5	≤1.2	5200-20000	5200-14000	7.5x4.5x1.0
WGLL-03900	3900	DC~3900	≤1.5	≤1.5	6000-13000	6250-8300	3.2x1.6x1.0

Ver.20190315